



Material Safety Data Sheet

SIKASIL-GP

SECTION 1 – Product and Company Identification

PRODUCT NAME: SIKASIL-GP
PRODUCT CODE: SIKASIL-GP Silicone Sealant
ADDRESS: Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
PHONE: (201) 933 - 8800
FAX: (201) 804 - 1076
EMERGENCY PHONE: (CHEMTREC) (800) 424 9300
International (CHEMTREC) (703) 527-3887
REVISION DATE : 11/05/10 SUPERSEDES: 12/03/08

SECTION 2 – COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

This product consists of a mixture/preparation.

CAS Number	Ingredient	Wt. %
17689-77-9	Ethyltriacetoxysilane	1-5
4253-34-3	Methyltriacetoxysilane	1-5

*The above components are hazardous as defined in 29 CFR 1910.1200

SECTION 3 – HAZARDS IDENTIFICATION

MAIN SYMPTOMS:

EYE: Direct contact irritates moderately with redness and swelling.
SKIN: A single short exposure (less than 24 hours) may irritate. Repeated prolonged contact (24 to 48 hours) may irritate moderately.
INHALATION: Irritates respiratory passages very slightly. Overexposure may cause drowsiness.
ORAL: May cause vomiting.
HMIS HAZARD CODES: Health: 2 Flammability: 1 Reactivity: 0 PPE: C

COMMENTS When heated to temperatures above 150°C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limit for formaldehyde.

SECTION 4 – FIRST-AID PROCEDURES

INHALATION: Remove to fresh air. If ill effects persist, get medical attention.
SKIN CONTACT: Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation develops or ill effects persist.
EYE CONTACT: Immediately flush with water for 15 minutes. Get medical attention.
INGESTION: Get medical attention.
COMMENTS: Treat according to person's condition and specifics of exposure.

SECTION 5 – FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Compatible with all usual extinguishing media



Material Safety Data Sheet

SIKASIL-GP

FIRE-FIGHTING PROCEDURES: Wear full protective clothing, positive pressure or pressure demand breathing apparatus and protective covering for exposed areas of the head. If large amount is involved, evacuate area..

FLASH POINT (CLOSED CUP): Greater than 212F (100C)

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: metal oxides, silicone dioxide, carbon oxides and traces of incompletely burned carbon compounds, nitrogen oxides and formaldehyde.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Observe all personal protective equipment recommendations described in Sections 5 and 8.

ENVIRONMENTAL PRECAUTIONS: Disposal of collected product, residues, and cleanup materials may be governmentally regulated. Observe all applicable local, state and Federal waste management regulations.

METHODS FOR CLEANING UP: Ventilate area. Contain spill. Evacuate unprotected personnel from hazard area. Wipe up or scrape up and contain for salvage or disposal. Cover with absorbent, place in approved drum; Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state, and federal reporting requirements may apply to spills or releases of this material into the environment. See applicable regulatory compliance information in Section 15.

SECTION 7 – HANDLING AND STORAGE

HANDLING: Assure good ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Do not take internally. Avoid breathing vapor.

STORAGE: Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.

SECTION 8 – EXPOSURE CONTROL AND PERSONAL PROTECTION

ENGINEERING CONTROLS:

LOCAL EXHAUST: Recommended

GENERAL VENTILATION: Recommended

PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Avoid eye contact. Use proper protection, safety glasses as a minimum.

SKIN AND BODY PROTECTION: Avoid skin contact. Protect hands with impervious rubber gloves and wear typical full cover clothing. Gloves must be checked before each use for signs of degradation and penetration and for proper functioning. Use nitrile or butyl rubber gloves.

RESPIRATORY PROTECTION: Avoid breathing of vapors. Wear appropriate, properly fitted NIOSH/MSHA approved respirator when the airborne contaminant levels exceed the exposure limits indicated on the MSDS. Follow respirator manufacturer's directions for respirator use.

HYGIENE MEASURES (INGESTION): Wash hands after handling and before eating.

Precautionary measures: Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally.

Note: These precautions are for room temperature handling. Use at elevated temperatures or aerosol spray applications may require added precautions.



Material Safety Data Sheet

SIKASIL-GP

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:	Solid (Paste)
ODOR:	Acetic acid (vinegar odor)
FLASHPOINT:	Greater than 65°C (150°F)
VAPOR PRESSURE (AT 100°F):	Not Applicable
VAPOR DENSITY:	Not Determined
DENSITY:	7.92 lbs/gal
SOLUBILITY IN WATER (%):	NIL
SPECIFIC GRAVITY (AT 77°F/25°C):	0.95
% VOLATILE BY VOLUME:	Not Determined
VOLATILE ORGANIC CONTENT (VOC):	Not Determined
FLASH POINT (SETAFLASH):	Greater than 100°C (212°F)
NOTE:	The above information is not intended for use in preparing product specifications.

SECTION 10 – STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable. No hazardous reactions when stored and handled according to prescribed instructions.
HAZARDOUS DECOMPOSITION PRODUCTS:	Thermal decomposition products as described in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

CHRONIC EXPOSURE:	
SKIN:	Repeat contact with skin may irritate moderately. Acetic acid may cause skin irritation.
INHALATION:	Vapor overexposure may irritate eyes, nose, and throat. Exposure to acetic acid may cause respiratory tract irritation, although chronic exposure may cause chronic bronchitis
ORAL:	Swallowing may have adverse effects depending on quantity ingested.
SPECIFIC EFFECTS:	This material contains the following components with the special hazards listed below. Carcinogens: None Known Teratogens: None Known Mutagens: None Known Reproductive toxins: None Known

SECTION 12 – ECOLOGICAL INFORMATION

Do not allow product to enter waste water drains, waterways or soil. However, when exposed to moisture and air in the environment, the product cures to a solid state in which no leach-able materials will be released.

SECTION 13 – DISPOSAL INFORMATION

PRODUCT DISPOSAL:	<u>RCRA Hazard Class (40 CFR 261)</u> When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO. State or local laws may impose additional regulatory requirements regarding disposal.
-------------------	---

SECTION 14 – TRANSPORT INFORMATION

<u>DOT Information (49CFR 172.101)</u>	
PROPER SHIPPING NAME:	Not Applicable
HAZARD CLASS:	Not Applicable
UN / NA NUMBER:	None
PACKING GROUP:	Not Applicable

SECTION 15 – REGULATORY INFORMATION



Material Safety Data Sheet

SIKASIL-GP

.INTERNATIONAL:

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Canadian DSL

All ingredients in this product are currently listed on the Canadian Domestic Substances List (DSL), and would not be considered new for the purposes of the Canadian Environmental Protection Act (CEPA).

Note:

The recipient of this product should be aware of the possible existence of additional local regulations, which may be applicable to this product.

SECTION 16 – OTHER INFORMATION

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.