

Pure Sine Wave Inverters

**DC to AC Inverters
2000 W / 3000 W**

- Premium pure sine inverters!
- Features Powersave Mode
- For RVs, boats, cars and trucks
- Innovative, compact design
- Optional remote available
- Dual GFCI receptacles & AC hardwire connections



The Superior Power of Pure Sine Wave

Go Power!™ Pure Sine Wave Inverters are the ultimate choice for appliances that demand a clean, pure source of AC power. The GP-SW2000 and SW3000 will run practically everything in your RV or cottage and still have pure power for the sensitive loads. Both feature a duplex GFCI receptacle and full overload protection.

Ideal for:

Kitchen Appliances - coffee makers, blenders, microwaves and refrigerators.

Office Equipment - computers, printers, fax machines and monitors.

Consumer Electronics - TVs, VCRs, stereos, lighting, fans, DVD players and satellite dishes.

Utility Truck Equipment - Power tools, battery chargers, test equipment, pumps, air compressors.

Use anywhere including:

- RVs and Campers
- Long Haul Trucks
- Boats
- Mobile Office
- Service Vehicles
- Emergency Vehicles
- Utility Trucks



The Go Power!™ GP-SW2000 W, GP-SW3000 W Inverters and the GP-SWR-B Remote are pictured above. (from top left to bottom right)

Specifications	GP-SW2000		GP-SW3000	
	12 V	24 V	12 V	24 V
Continuous Output Power	2000 W		3000 W	
Surge Rating	4000 W		6000 W	
Output Waveform	Pure Sine Wave			
Output Voltage ± 3%	115 VAC RMS			
Output Frequency ± 0.05%	60 Hz			
Input Voltage	10.5 - 15 VDC	21 - 30 VDC	10.5 - 15 VDC	21-30 VDC
Efficiency	85-92%			
No Load Current Draw / Powersave Protection	2.8 A / 0.6 A	1.5 A / 0.3 A	2 A / 0.55 A	1.6 A / 0.35 A
Overload, Short Circuit, Reverse Polarity (Fuse), Over/Under Input voltage, Over Temperature	Overload, Short Circuit, Reverse Polarity (Fuse), Over/Under Input voltage, Over Temperature			
Low Battery Alarm ± 2%	10.5 V - 10 V	21 V - 20.5 V	10.5 V - 10 V	21 V - 20.5 V
Low Battery Shut-Down ± 2%	10 V	21 V	10 V	21 V
Operating Temperature Range	0 - 40°C / 32°F - 104°F			
Storage Temperature Range	-30°C - 70°C / -22°F - 158°F			
Cooling	Thermostatically Controlled Fan			
AC Receptacle	Dual GFCI			
Dimensions (LxWxH) mm	422 x 208 x 166		452 x 208 x 166	
inches	16.6 x 8.2 x 6.5		17.8 x 8.2 x 6.5	
Weight kg / lbs	9.5 / 21		9.8 / 22	
Warranty	2 years			
Inverter Install Kit	GP-DC-KIT4	GP-DC-KIT3	GP-DC-KIT5	GP-DC-KIT3
UPC	8-39085-00068-7	8-39085-00069-4	8-39085-00070-0	8-39085-00071-7
Remotes	GP-SWR-B-12	GP-SWR-B-24	GP-SWR-B-12	GP-SWR-B-24

*Specifications subject to change without notice



Carmanah®
www.carmanah.com

the POWER to GO anywhere!

In US contact: 866-247-6527 In Canada contact: 800-667-6527 Toll Free Fax: 866-607-6527
sales@gpelectric.com www.gpelectric.com

